



SCAN HERE



**SOFTRAK**

**HIAB 022T3**

- 600mm Bridgestone rubber track system.
- 67hp turbo diesel engine.
- High level air intake with high capacity cooling fan.
- Single lever control for steering, speed control and throttle.
- High torque two speed (14kph/7kph) wheel motors with integral oil immersed emergency and parking brakes.
- Three man, fully glazed cab with suspension seat for driver, lap restraints, grab handles and cab heating and ventilation system.
- Full instrumentation with tachometer/hour meter, water temp and fuel gauges & automatic engine shutdown on low oil or high water temperature.
- Front and rear work lights.
- 50mm rear tow hook and clevis.

**CRANE**

HIAB 022T-2 Crane with 2 section hydraulic extension (3.1M) and manually operated hydraulic valve

Options: 3 section hydraulic extension boom from 3.1m to 4.1.

G180 Timber Grapple (850mm tip to tip), FR-7 Rotator (Continuous rotation) and 5 lever valve block, hoses, fitting etc

Weight ..... Approx 245 kg

© LOGLOGIC. We reserve the right to change the specification without notice.

The Loglogic Softrak is a multi-purpose, low ground pressure, rubber tracked vehicle. On environmentally sensitive areas such as wetland habitats its extremely low ground pressure and unique flexible rubber track ensures minimal damage to both flora and fauna. The 2,000kg payload Softrak can be fitted with a range of compact cranes which enables loads to be transported and craned into previously inaccessible locations.

For use on soft terrains cranes of up to 20.5kN/m can be fitted without using stabilisers, minimising time taken to setup and offload and eliminating problems with the stabilisers sinking in soft ground. This allows loads of up to 500kg to be lifted at 4.2m or 1,730kg at 1.25m. making it ideal for handling barrels, kerb stones, manhole covers, pumps, traffic barriers, Portaloo's, industrial equipment and most other medium weight machinery. Larger cranes fitted with stabilisers can be mounted on the Softrak where loads of up to 2000kg need to be safely handled.



**PALFINGER PC2700B**



**HIAB 017T3**



**HIAB**

**SOFTRAK CRANES SYSTEMS**